

Waterproof Devices

Description



The 48 WATERPROOF Series ensures a **IP65 Protection Degree** in electrical installations in wet and dusty spaces.

Manufactured in technical thermoplastic (**shock resistant**), the 48 WATERPROOF Series is the best solution for installations in garages, gardens, swimming pools, industrial spaces, etc.

BR - White (RAL 9003) and **CZ** - Grey (RAL 7035)

Characteristics

Mechanisms in Technical Thermoplastic - resistant material, non-conductive.

Control Devices

10 A - 250 V~
Screw connection. It allows the usage of rigid and flexible cable.
Pilot Light.
In accordance with IEC/EN 60669-1 Standard, tested according to 19.3:

Relationship between rated current of the switch and rated power of the SBL circuit	
Rated current of the switch, In [A]	Rated power of the SBL circuit [W]
In ≤ 10	100
10 < In ≤ 13	150
13 < In ≤ 16	200
16 < In ≤ 20	250


SBL - Self Ballasted Lamp (CFL or LED)

Energy Sockets

Schuko and French Sockets
16 A - 250 V ~
Screw connection.
In accordance with IEC 60884-1; DIN VDE 0620-1 (Schuko) and NF C 61-314 (French) Standards
Energy Sockets: Single, Double Vertical and Horizontal

Variety of Functions: Control Devices, Blinds Control, Energy Sockets, etc.

Draining Holes: All the products of the WATERPROOF 48 Series have two pre-drilled draining holes.
Depending on the mounting position of the product, the draining hole pointing to the lower part of the base must be open.



Dimensions (mm)

