

Surface Mounting Devices

Description



The **2600** Series takes us into the past, bringing back the *vintage* trend.

Easy to assemble, the **2600** Series is the ideal product to surface mounting installations and **house remodeling**.

**MF** - Ivory

Characteristics

Mechanisms in Technical Thermoplastic - resistant material, non-conductive.  
Surface mounted devices appliances must be fitted with “a plastic round base” made of insulating material.

Control Devices

**10 A - 250 V~**  
Screw connection. It allows the usage of rigid and flexible cable.  
In accordance with IEC/EN 60669-1 Standard, tested according to 19.3:

| Relationship between rated current of the switch and rated power of the SBL circuit |                                    |
|-------------------------------------------------------------------------------------|------------------------------------|
| Rated current of the switch, In [A]                                                 | Rated power of the SBL circuit [W] |
| $I_n \leq 10$                                                                       | 100                                |
| $10 < I_n \leq 13$                                                                  | 150                                |
| $13 < I_n \leq 16$                                                                  | 200                                |
| $16 < I_n \leq 20$                                                                  | 250                                |

SBL - Self Ballasted Lamp (CFL or LED)

Energy Sockets

**Schuko Sockets**  
**16 A - 250 V ~**  
Screw connection.  
In accordance with IEC 60884-1 Standard

Dimensions (mm)

